

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 09-259385

(43) Date of publication of application : 03.10.1997

(51)Int.CI.

**G08G 1/005**

**G06F 17/30**

**G08G 1/137**

H04M 11/08

(21)Application number : 08-065620

(71)Applicant : NIPPON TELEG & TELEPH  
CORP <NTT>

(22)Date of filing : 22.03.1996


(72)Inventor : **NOMURA TETSUYA**  
**KINOHARA SEIJI**  
**YADA KENICHI**

### (54) ROAD GUIDING SYSTEM

**(57)Abstract:**

**PROBLEM TO BE SOLVED:** To provide a road guiding system suitable for the utilization of a walker as well for easily intuitively recognizing a direction to advance at each important part to a destination based on the information of the destination and a present location.

**SOLUTION:** A user instructs and inputs the destination and the present location from a terminal 2 and transmits them through a PHS public CS 4 and an ISDN network 3 to a center device 1. The center device 1 selects an optimum route, the route for minimizing a moving distance for instance, from the received information of the destination and the present location and transmits the direction to advance to the terminal 2 along with the scenery video images of the places stored in the center device 1. The terminal 2 displays the received direction to advance and scenery video images on a monitor screen. In this case, the center device 1 facilitates the discovery of a building or the like to be a guide by switching the scenery video images to be displayed corresponding to the utilization time band of a road guiding service such as daytime, evening and nighttime. In the case that the present location is unclear, a position detected from the time difference of reference signals received from plural GPS satellites 5 is defined as the present location.



## LEGAL STATUS

[Date of request for examination] 28.10.1999

[Date of sending the examiner's decision of rejection] 06.02.2001

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

**\* NOTICES \***

JPO and NCIPi are not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

---

**DETAILED DESCRIPTION**

---

[Detailed Description of the Invention]

[0001]

[Field of the Invention] This invention relates to the system to which it shows a user to the destination with a scene image.

[0002]

[Description of the Prior Art] The navigation equipment using GPS (Global Positioning System) is put in practical use as an example of the equipment to guide. This navigation equipment presumes a location from the time difference of the reference signal received from two or more satellites, and displays this location with the map mentioned in CD-ROM etc. on monitor display.

[0003] Although the great portion of commercial navigation equipment is a mounted mold, the equipment which a pedestrian can carry is also developed. The navigation equipment of a mounted mold consists of two or more components, such as a sensor which supervises the run state of a car besides a monitor / antenna / body. The point that the navigation equipment which a pedestrian can carry is the map with which the contents of a display were recorded on CD-ROM etc. is the same as the equipment of a mounted mold, the user itself needs to understand the contents of the map and needs to take correspondence with the notation on a map, and an actual scene.

[0004] On the other hand, the false solidification of the display on monitor display is carried out for not the map itself but a road, a building, etc. with CG (computer graphics) technique, and the method displayed in the style of a bird's-eye view image is proposed.

[0005]

[Problem(s) to be Solved by the Invention] First, since the sensor which supervises the run state of a car consists of two or more components and the navigation equipment of a mounted mold is premised on use with a car also for the display format on monitor display besides the monitor / antenna / body, there is a problem of not being suitable in use of a pedestrian.

[0006] On the other hand, with the navigation equipment which a pedestrian can carry, the point that the contents of a display are the maps recorded on CD-ROM etc. is the same as the equipment of a mounted mold, and since the user itself needs to understand the contents of the map and needs to take correspondence with the notation on a map, and an actual scene, a problem is in user-friendliness. Since a field of view is especially restricted at Nighttime etc., it is difficult to discover the target on a map, and user-friendliness worsens.

[0007] The activity which not the map itself but the method which carries out false solidification, and which is displayed in the style of a bird's-eye view image numerical-model-izes a scene for a monitor display, and inputs into CD-ROM etc. is not only required, but since it is difficult, a user needs to use imaginative power in contrast with an actual scene, and individual difference produces inputting all objects in extent of use.

[0008] Moreover, with navigation equipment [ more than ], since CD-ROM etc. cannot perform modification of the contents of a display, when offering the newest information / emergency intelligence, it has a problem.

[0009] Guidance intuitive [ the direction which should progress in the key point which goes to the destination based on the information on the destination and a its present location ], and intelligible is possible, and this invention aims at the guidance system distribution also suitable for pocket use of a pedestrian.

[0010]

[Means for Solving the Problem] In order to attain the above-mentioned purpose, the 1st invention by this invention A means to transmit the means which directs / inputs the destination and a its present location, said destination, and a its present location to center equipment, The terminal which has the direction which should progress from center equipment, a means to receive a scene image, and the means which carries out scene graphic display to said received direction which should progress, A means to choose the optimal point to point path of a means to receive the destination and a its present location, said received destination, and a its present location from said terminal, A means to accumulate the scene image which can be searched from the location in a path at least, and a means to transmit the direction which should progress based on said optimal selected path to said terminal with said scene image searched from the location in said optimal path, Let the guidance system characterized by having said center equipment which \*\*\*\* be a means.

[0011] Moreover, a means by which the 2nd invention by this invention accumulates the scene image in center equipment in the above-mentioned guidance system A means in said center equipment to transmit the direction which should progress to a terminal with a scene image, by the ability searching a scene image from the utilization-time band of the location in a path, and guidance service It is characterized by what is transmitted to said terminal with said scene image which searched the direction which should progress based on the optimal selected path from the utilization-time band of the location in said optimal path, and guidance service.

[0012] Furthermore, in the above guidance system, the 3rd invention by this invention newly equips a terminal with a location detection means, and is characterized by the thing using the location detection output of this location detection means as a its present location.

[0013] This invention based on the information on the destination and its present location which the user directed / inputted from the terminal While performing intuitive and intelligible guidance by displaying on a terminal the scene image which chose a path with the optimal center equipment, for example, the path from which migration length serves as min, and accumulated it in the direction which should progress, and center equipment, and using for guidance Renewal of a scene image should be made easy, and the configuration of a terminal should be simplified, and it should be suitable also for a pedestrian's cellular phone.

[0014] Furthermore, by changing the scene image which should be displayed in the daytime according to the utilization-time band of guidance services, such as /twilight / night, discovery of the building used as a mark etc. is made easy, and it considers as a much more intuitive and intelligible thing.

[0015]

[Embodiment of the Invention] Hereafter, a drawing explains the gestalt of operation of this invention in detail.

[0016] Drawing 1 is the whole system block diagram showing the example of 1 operation gestalt of this invention, and, as for 1, center equipment and 2 are [ the PHS public CS by whom a terminal and 3 were connected to the ISDN network and 4 was connected to the ISDN network 3, and 5 ] two or more GPS Satellites.

[0017] Drawing 2 is the block diagram of the center equipment 1 of this system, it connects with the bus of a control section 16, and the Management Department 11, such as location data / scene image, the scene image are recording section 12, the GPS signal receive section 13, the line control section 14 containing a modem, and the optimal-path selection section 15 are constituted. GPS antenna 13a is connected to the GPS signal receive section 13, and the line control section 14 is connected to the ISDN network 3. The GPS signal receive section 13 receives a reference signal from two or more satellites 5 through GPS antenna 13a, and presumes a location from the time difference of those reference signals.

[0018] Drawing 3 is the block diagram of the terminal 2 of this system, it connects with the bus of a control section 26, and the display 21 with a touch panel, the GPS signal receive section 22, the transceiver section 23 containing a modem, the path storage section 24, the scene image storage section 25, and the voice output section 27 are constituted. GPS antenna 22a is connected to the GPS signal receive section 22, the line control section 14 is connected to the ISDN network 3, and the loudspeaker 28 is connected to the output side of the voice output section 27. The GPS signal receive

section 22 receives a reference signal from two or more satellites 5 through GPS antenna 22a, and presumes a location from the time difference of those reference signals.

[0019] Drawing 4 is drawing showing a format of the Management Department 11, such as location data / scene image of the above-mentioned center equipment 1, and consists of scene image management data which consist of the scene image ID 116 and Mark ID 117 according to time zones, such as /twilight / night, every location ID 111 management data, such as a location which consists of a direction ID 112, the adjoining location ID 113, distance 114, and a target ID 115, and in the daytime.

[0020] In the above configuration, center equipment 1 and a terminal 2 perform data communication with a modem signal via PHS antenna 23a of the line control section 14 of center equipment 1, the ISDN network 3, the PHS public CS 4, and a terminal 2, and the transceiver section 23.

[0021] Drawing 5 is the explanatory view of this example of an operation gestalt of operation.

[0022] Hereafter, according to the above-mentioned drawing, actuation of this example of an operation gestalt is explained.

[0023] (1) Employment of location data and the are recording book system of a scene image is preceded. To the Management Department 11, such as location data / scene image of center equipment 1, as management data, such as a location A direction ID 112 is set up to all the directions corresponding to the name of a place/lot number to which a user may go every location ID 111, and the data of target ID115 grade in which the distance 114 between the adjoining location ID 113 and a location ID, the building which serves as a target further are shown are stored.

[0024] The mark ID 117 which shows the building which serves as a mark the scene image ID 116 which shows the scene image according to utilization-time band accumulated in the scene image are recording section 12 every direction ID 112 as scene image management data, and in it is accumulated in coincidence.

[0025] Compared with the method which a user purchases / uses, the location data of center equipment 1 and a scene image can carry out renewal of the CD-ROM etc. of proper, and it can respond to a detour measure, common initiation / halt of a facility, etc. accompanying opening of traffic of a road, and construction/accident flexibly. Offer of the scene image in the real time is also possible by using the image from supervisory equipment etc. also to the variable field place of a traffic especially irregularly to an event etc.

[0026] In addition, the same stereo shall be shown when the same code is assigned by the target ID 115 and Mark ID 117 of the Management Department 11, such as location data / scene image.

[0027] (2) The input user of positional information directs / inputs the destination and a his present location from the software keyboard displayed on the display 21 with a touch panel of a terminal 2. It is transmitted from the line control section 14 of a terminal 2, and the destination and their present location which were directed / inputted are received in the transceiver section 23 of center equipment 1 through the PHS public CS 4 and the ISDN network 5. Center equipment 1 directs reinput to a terminal 2, when the positional information which corresponds the destination and its present location which were directed / inputted from a terminal 2 as compared with the location ID 111 of the Management Department 11, such as location data / scene image, is not registered.

[0028] When a its present location is unknown, the location detection output of the GPS signal receive section 22 of a terminal 2 is transmitted to center equipment 1, and positional information is acquired by amending further with the location detection output of the GPS signal receive section 13 of center equipment 1. A modem signal performs data communication between the line control section 14 of center equipment 1, and the transceiver section 23 of a terminal 2 including transmission of the below-mentioned scene image.

[0029] the difference [ positional information / of a precision required for employment of this system ] on the basis of the installation location of center equipment 1 -- it is obtained by the GPS method.

[0030] (3) The optimal-path selection section 15 of the selection center equipment 1 of an optimal path chooses the path from which migration length serves as min from management data, such as a location accumulated in the information on the destination and its present location which received from the terminal 2, and the Management Department 11, such as location data / scene image, as an optimal path 31, for example in drawing 5 . A selection result is outputted as a pair of sequence of

the direction ID 112 which shows the location ID 111 which shows a shunt 32, and the direction which should progress.

[0031] (4) The selection center equipment 1 of a scene image searches and chooses the scene image which should be displayed from the time zone of time of day with the service request from the output and user of the optimal-path selection section 15. For example, in drawing 5, to the service request in the night from the present location shown with the name of a place / lot number i, the image i-2-3 to which the scene image ID 116 of the direction ID 2 of drawing 4 corresponds is read from the scene image recording section 12, and it transmits to a terminal 2. A mark i-2-2 is also doubled and transmitted as a mark ID 117 corresponding to coincidence.

[0032] In the contents of the mark ID 117, a scene image accumulates such information which received the terminal 2 for every shunt in the path storage section 24 at the scene image storage section 25, respectively.

[0033] (5) The display terminal 2 of a scene image displays the scene image received from center equipment 1 on the monitor display of the display 21 with a touch panel. In that case, the building corresponding to the mark ID 117 read from the path storage section 24 etc. is expressed as a pointer etc., and discovery of the direction to which a user should go is supported.

[0034] Furthermore, the control section 26 of a terminal 2 performs location presumption by the GPS signal for every setup time, and processes changing a display image, when below setting distance is approached to the shunt 32 accumulated in the path storage section 24, or telling about by the beep sound from the voice output section 27, when a user separates from an optimal path 31 beyond setting distance etc.

[0035] In addition, although the GPS signal was used for location presumption in said example of an operation gestalt, the configuration which does not mount the GPS signal receive section supposing the use in the city area equipped fully with the lot number display is also possible.

[0036] Although the communication link between center equipment and a terminal showed the example which uses a modem signal with PHS, it is also possible to take the same configuration with a cellular phone. Moreover, it is also possible to realize by the digital data communication link of PHS.

[0037]

[Effect of the Invention] As explained above, according to this invention, a user can find out the direction which should progress easily by comparing the scene image displayed on the monitor display of a terminal, and an actual scene.

[0038] Moreover, the scene image of center equipment can be updated suitably and offer of the newest information / emergency intelligence with difficult correspondence of it is attained in CD-ROM.

[0039] Moreover, especially when a scene image is divided into a utilization-time band and changed, the arrival also of Nighttime whose prospect is not effective to the destination is attained easily.

[0040] Furthermore, especially, when a its present location is specified using location detection means, such as GPS, also when a its present location is unknown, guidance service is attained.

---

[Translation done.]

\* NOTICES \*

JPO and NCIP are not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

---

CLAIMS

---

[Claim(s)]

[Claim 1] A means to transmit the means which directs / inputs the destination and a its present location, said destination, and a its present location to center equipment, The terminal which has the direction which should progress from center equipment, a means to receive a scene image, and the means which carries out scene graphic display to said received direction which should progress, A means to choose the optimal point to point path of a means to receive the destination and a its present location, said received destination, and a its present location from said terminal, A means to accumulate the scene image which can be searched from the location in a path at least, and a means to transmit the direction which should progress based on said optimal selected path to said terminal with said scene image searched from the location in said optimal path, The guidance system characterized by having said center equipment which \*\*\*\*.

[Claim 2] A means to accumulate the scene image in center equipment A means in said center equipment to transmit the direction which should progress to a terminal with a scene image, by the ability searching a scene image from the utilization-time band of the location in a path, and guidance service The guidance system according to claim 1 characterized by what is transmitted to said terminal with said scene image which searched the direction which should progress based on the optimal selected path from the utilization-time band of the location in said optimal path, and guidance service.

[Claim 3] The guidance system according to claim 1 or 2 which newly equips a terminal with a location detection means, and is characterized by the thing using the location detection output of this location detection means as a its present location.

---

[Translation done.]

\* NOTICES \*

JPO and NCIP are not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

---

DESCRIPTION OF DRAWINGS

---

[Brief Description of the Drawings]

[Drawing 1] The system configuration Fig. showing the example of 1 operation gestalt of this invention

[Drawing 2] The block block diagram of the center equipment of the system in the above-mentioned example of an operation gestalt

[Drawing 3] The block block diagram of the terminal of the system in the above-mentioned example of an operation gestalt

[Drawing 4] Drawing showing a format of the Management Department, such as location data / scene image in the above-mentioned center equipment

[Drawing 5] The explanatory view of the above-mentioned example of an operation gestalt of operation

[Description of Notations]

1 -- Center equipment

11 -- The Management Department, such as location data / scene image

111 -- Location ID

112 -- Direction ID

113 -- Adjoining location ID

114 -- Distance

115 -- Target ID

116 -- Scene image ID

117 -- Mark ID

12 -- Scene image are recording section

13 -- GPS signal receive section

14 -- Line control section

15 -- Optimal-path selection section

16 -- Control section

2 -- Terminal

21 -- Display with a touch panel

22 -- GPS signal receive section

23 -- Transceiver section

24 -- Path storage section

25 -- Scene image storage section

26 -- Control section

27 -- Voice output section

31 -- Optimal path

32 -- Shunt

3 -- ISDN network

4 -- PHS public CS

5 -- Terminal

---

[Translation done.]




## \* NOTICES \*

JPO and NCIP are not responsible for any damages caused by the use of this translation.


1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

## DRAWINGS


[Drawing 1]




[Drawing 2]



[Drawing 3]



[Drawing 5]



[Drawing 4]

111. 位置 ID	位置等管理データ				景観映像管理データ		
	112. 方向 ID	113. 隣接位置 ID	114. 距離	115. 目標 ID	時間帯	116. 景観映像 ID	117. 目印 ID
...	...	...	...	...		...	...
地名／地番 i	方向 ID1	地名／地番 p	距離 p	目標 i-1-1, i-1-2	日中	映像 i-1-1	115. に同じ
					夕暮れ	映像 i-1-2	目印 i-1-2
					夜間	映像 i-1-3	目印 i-1-2
	方向 ID2	地名／地番 q	距離 q	目標 i-2-1, i-2-2, i-2-3	日中	映像 i-2-1	115. に同じ
					夕暮れ	映像 i-2-2	目印 i-2-2, i-2-3
					夜間	映像 i-2-3	目印 i-2-2
	...	...	...	...		...	...
...	...	...	...	...		...	...
地名／地番 j	方向 ID1	地名／地番 x	距離 x	目標 j-1-1	日中	映像 j-1-1	115. に同じ
					夕暮れ	映像 j-1-2	115. に同じ
					夜間	映像 j-1-3	無し
	方向 ID2	地名／地番 y	距離 y	目標 j-2-1, j-2-2	日中	映像 j-2-1	目印 j-2-1
					夕暮れ	映像 j-2-2	目印 j-2-2
					夜間	映像 j-2-3	目印 j-2-2
	...	...	...	...		...	...
...	...	...	...	...		...	...

[Translation done.]

(51) Int.Cl. <sup>8</sup>	識別記号	庁内整理番号	F I	技術表示箇所
G 0 8 G 1/005			G 0 8 G 1/005	
G 0 6 F 17/30			1/137	
G 0 8 G 1/137			H 0 4 M 11/08	
H 0 4 M 11/08			G 0 6 F 15/40	3 7 0 C

審査請求 未請求 請求項の数 3 O L (全 7 頁)

(21) 出願番号 特願平8-65620

(22) 出願日 平成8年(1996)3月22日

(71) 出願人 000004226

日本電信電話株式会社

東京都新宿区西新宿三丁目19番2号

(72) 発明者 野村 哲也

東京都新宿区西新宿3丁目19番2号 日本  
電信電話株式会社内

(72) 発明者 木ノ原 誠司

東京都新宿区西新宿3丁目19番2号 日本  
電信電話株式会社内

(72) 発明者 矢田 健一

東京都新宿区西新宿3丁目19番2号 日本  
電信電話株式会社内


(74) 代理人 弁理士 志賀 富士弥

(54) 【発明の名称】 道案内システム

(57) 【要約】

【課題】 目的地と現在地の情報を基に、目的地への所要所まで進むべき方向が直感的で分かりやすく、歩行者の利用にも適した道案内システムを提供する。

【解決手段】 利用者が、端末2から目的地および現在地を指示/入力し、PHS公衆CS4、ISDN網3を介してセンタ装置1に送信する。センタ装置1は、受信した目的地および現在地の情報から最適な経路、例えば移動距離が最小となる経路を選択し、進むべき方向をセンタ装置1に蓄積した当該場所の景観映像とともに端末2へ送信する。端末2は、受信した進むべき方向と景観映像をモニタ画面上に表示する。ここで、センタ装置1は、日中/夕暮れ/夜間など道案内サービスの利用時間帯に応じて表示すべき景観映像を切り替えることにより、目印となる建物などの発見を容易にする。現在地が不明な場合には、複数のGPS衛星5から受信した基準信号の時間差から検出した位置を現在地とする。



## 【特許請求の範囲】

【請求項1】 目的地および現在地を指示／入力する手段、前記目的地および現在地をセンタ装置に送信する手段、センタ装置から進むべき方向と景観映像を受信する手段、および前記受信した進むべき方向と景観映像表示する手段、を有する端末と、

前記端末から目的地および現在地を受信する手段、前記受信した目的地および現在地の二点間の最適な経路を選択する手段、少なくとも経路中の場所から検索可能な景観映像を蓄積する手段、および前記選択された最適な経路に基づいて進むべき方向を前記最適な経路中の場所から検索した前記景観映像とともに前記端末へ送信する手段、を有する前記センタ装置と、

を有することを特徴とする道案内システム。

【請求項2】 センタ装置における、景観映像を蓄積する手段は、経路中の場所と道案内サービスの利用時間帯から景観映像を検索可能なものであり、

前記センタ装置における、進むべき方向を景観映像とともに端末へ送信する手段は、選択された最適な経路に基づいて進むべき方向を前記最適な経路中の場所と道案内サービスの利用時間帯から検索した前記景観映像とともに前記端末へ送信する、

ことを特徴とする請求項1記載の道案内システム。

【請求項3】 端末に、新たに位置検出手段を備え、該位置検出手段の位置検出出力を現在地として用いる、ことを特徴とする請求項1または請求項2記載の道案内システム。

## 【発明の詳細な説明】

## 【0001】

【発明の属する技術分野】本発明は、景観映像により利用者を目的地まで道案内するシステムに関するものである。

## 【0002】

【従来の技術】道案内する装置の例としては、GPS (Global Positioning System) を利用したナビゲーション装置が実用化されている。このナビゲーション装置は、複数の衛星から受信した基準信号の時間差から位置を推定し、この位置をモニタ画面上にCD-ROM等に収録された地図とともに表示するものである。

【0003】市販のナビゲーション装置の大部分は車載型であるが、歩行者が携帯可能な装置も開発されている。車載型のナビゲーション装置は、モニタ／アンテナ／本体以外にも車両の走行状態を監視するセンサなど複数の構成部品からなる。歩行者が携帯可能なナビゲーション装置は、表示内容がCD-ROM等に収録された地図である点は車載型の装置と同じであり、利用者自身が地図の内容を理解し地図上の表記と実際の景観との対応をとる必要がある。

【0004】一方、モニタ画面上の表示を地図そのもの

ではなく、道路、建物等をCG (コンピュータグラフィックス) 技術により疑似立体化し、鳥瞰映像風に表示する方法が提案されている。

## 【0005】

【発明が解決しようとする課題】まず、車載型のナビゲーション装置は、モニタ／アンテナ／本体以外にも車両の走行状態を監視するセンサなど複数の構成部品からなり、モニタ画面上の表示様式も車両での利用を前提としているため、歩行者の利用には適さないという問題がある。

【0006】一方、歩行者が携帯可能なナビゲーション装置では、表示内容がCD-ROM等に収録された地図である点は車載型の装置と同じであり、利用者自身が地図の内容を理解し地図上の表記と実際の景観との対応をとる必要があるため、使い勝手に問題がある。特に、夜間などは視界が限られるため、地図上の目標を探し出すことが難しく、使い勝手は悪くなる。

【0007】モニタ表示を地図そのものではなく、疑似立体化して鳥瞰映像風に表示する方法は、景観を数値モデル化してCD-ROM等に入力する作業が必要だけでなく、全ての対象を入力することは困難なため、利用者が実際の景観との対比において想像力を働かせる必要があり、利用の程度に個人差が生ずる。

【0008】また、以上のナビゲーション装置では、CD-ROM等は表示内容の変更ができないため、最新情報／緊急情報を提供する上で問題がある。

【0009】本発明は、目的地および現在地の情報を基にして、目的地に向かう所要所において進むべき方向が直感的で分かりやすい道案内が可能であり、歩行者の携帯利用にも適した道案内システムの提供を目的とするものである。

## 【0010】

【課題を解決するための手段】上記の目的を達成するため、本発明による第1の発明は、目的地および現在地を指示／入力する手段、前記目的地および現在地をセンタ装置に送信する手段、センタ装置から進むべき方向と景観映像を受信する手段、および前記受信した進むべき方向と景観映像表示する手段、を有する端末と、前記端末から目的地および現在地を受信する手段、前記受信した目的地および現在地の二点間の最適な経路を選択する手段、少なくとも経路中の場所から検索可能な景観映像を蓄積する手段、および前記選択された最適な経路に基づいて進むべき方向を前記最適な経路中の場所から検索した前記景観映像とともに前記端末へ送信する手段、を有する前記センタ装置と、を有することを特徴とする道案内システムを手段とする。

【0011】また、本発明による第2の発明は、上記の道案内システムにおいて、センタ装置における、景観映像を蓄積する手段は、経路中の場所と道案内サービスの利用時間帯から景観映像を検索可能なものであり、前記

センタ装置における、進むべき方向を景観映像とともに端末へ送信する手段は、選択された最適な経路に基づいて進むべき方向を前記最適な経路中の場所と道案内サービスの利用時間帯から検索した前記景観映像とともに前記端末へ送信する、ことを特徴とする。

【0012】さらに、本発明による第3の発明は、以上の道案内システムにおいて、端末に、新たに位置検出手段を備え、該位置検出手段の位置検出出力を現在地として用いる、ことを特徴とする。

【0013】本発明は、利用者が端末から指示/入力した目的地および現在地の情報を基に、センタ装置が最適な経路、例えば移動距離が最小となる経路を選択し、進むべき方向とセンタ装置に蓄積した景観映像を端末に表示して道案内に用いることにより、直感的で分かりやすい道案内を行うとともに、景観映像の更新を容易にし、かつ、端末の構成を単純化して歩行者の携帯にも適したものとする。

【0014】さらに、日中/夕暮れ/夜間など道案内サービスの利用時間帯に応じて表示すべき景観映像を切り替えることにより、目印となる建物などの発見を容易にし、一層直感的で分かりやすいものとする。

【0015】

【発明の実施の形態】以下、本発明の実施の形態を図面により詳しく説明する。

【0016】図1は本発明の一実施形態例を示すシステムの全体構成図であり、1はセンタ装置、2は端末、3はISDN網、4はISDN網3に接続されたPHS公衆CS、5は複数のGPS衛星である。

【0017】図2は本システムのセンタ装置1の構成図であり、位置データ/景観映像等管理部11、景観映像蓄積部12、GPS信号受信部13、モデムを含む回線制御部14および最適経路選択部15が、制御部16のバスに接続されて構成されている。GPS信号受信部13にはGPSアンテナ13aが接続され、回線制御部14はISDN網3に接続されている。GPS信号受信部13は、GPSアンテナ13aを通して複数の衛星5から基準信号を受信し、それらの基準信号の時間差から位置を推定する。

【0018】図3は本システムの端末2の構成図であり、タッチパネル付表示部21、GPS信号受信部22、モデムを含む送受信部23、経路記憶部24、景観映像記憶部25、および音声出力部27が、制御部26のバスに接続されて構成されている。GPS信号受信部22にはGPSアンテナ22aが接続され、回線制御部14はISDN網3に接続され、音声出力部27の出力側にはスピーカ28が接続されている。GPS信号受信部22は、GPSアンテナ22aを通して複数の衛星5から基準信号を受信し、それらの基準信号の時間差から位置を推定する。

【0019】図4は上記センタ装置1の位置データ/景

観映像等管理部11のフォーマットを示す図であり、位置ID111毎に、方向ID112、隣接位置ID113、距離114および目標ID115からなる位置等管理データ、ならびに日中/夕暮れ/夜間といった時間帯別の景観映像ID116、目印ID117からなる景観映像管理データから構成されている。

【0020】以上の構成において、センタ装置1と端末2とは、センタ装置1の回線制御部14、ISDN網3、PHS公衆CS4、端末2のPHSアンテナ23a、送受信部23を経由して、例えばモデム信号によりデータ通信を行う。

【0021】図5は本実施形態例の動作説明図である。

【0022】以下、上記図面に従って本実施形態例の動作を説明する。

【0023】(1)位置データおよび景観映像の蓄積  
本システムの運用に先立ち、センタ装置1の位置データ/景観映像等管理部11に、位置等管理データとして、地名/地番に対応する位置ID111毎に利用者が進む可能性のある全ての方向に対して方向ID112を設定し、隣接位置ID113、位置ID間の距離114、さらに目標となる建物等を示す目標ID115等のデータを蓄積する。

【0024】同時に、景観映像管理データとして、方向ID112毎に、景観映像蓄積部12に蓄積された利用時間帯別の景観映像を示す景観映像ID116、その中で目印となる建物等を示す目印ID117を蓄積する。

【0025】CD-ROM等を利用者が購入/使用する方式に比べて、センタ装置1の位置データ、景観映像ともに適宜更新でき、道路の開通、工事/事故に伴う迂回措置、施設の共用開始/停止などに柔軟に対応可能である。特に、催し物などで不定期に通行量の変化する場所に対しても、監視装置等からの映像を利用することにより実時間での景観映像の提供も可能である。

【0026】なお、位置データ/景観映像等管理部11の目標ID115と目印ID117で同一のコードが割り当てられた場合は同一実体を示すものとする。

【0027】(2)位置情報の入力

利用者は、目的地および現在地を端末2のタッチパネル付き表示部21に表示されるソフトキーボード等から指示/入力する。指示/入力された目的地および現在地は、端末2の回線制御部14から送信され、PHS公衆CS4、ISDN網5を介してセンタ装置1の送受信部23で受信される。センタ装置1は、端末2から指示/入力された目的地および現在地を位置データ/景観映像等管理部11の位置ID111と比較し、該当する位置情報が登録されていない場合は端末2に再入力を指示する。

【0028】現在地が不明の場合は、端末2のGPS信号受信部22の位置検出出力をセンタ装置1に送信し、さらにセンタ装置1のGPS信号受信部13の位置検出

出力で補正することにより位置情報を得る。後述の景観映像の伝送を含めて、センタ装置1の回線制御部14と端末2の送受信部23間でのデータ通信はモデム信号により行う。

【0029】本システムの運用に必要な精度の位置情報はセンタ装置1の設置位置を基準とする差分GPS方式により得られる。

#### 【0030】(3) 最適経路の選択

センタ装置1の最適経路選択部15は、端末2から受信した目的地および現在地の情報と、位置データ/景観映像等管理部11に蓄積された位置等管理データから、例えば図5において、移動距離が最小となる経路を最適経路31として選択する。選択結果は、通過点32を示す位置ID111と進むべき方向を示す方向ID112の対の系列として出力する。

#### 【0031】(4) 景観映像の選択

センタ装置1は、最適経路選択部15の出力と利用者からのサービス要求があった時刻の時間帯から表示すべき景観映像を検索、選択する。例えば図5において、地名/地番iで示される現在地からの夜間のサービス要求に対しては、図4の方向ID2の景観映像ID116の該当する映像i-2-3を景観映像蓄積部12から読み出し端末2に送信する。同時に、対応する目印ID117として目印i-2-2も合わせて送信する。

【0032】端末2は、受信したこれらの情報を、目印ID117の内容は経路記憶部24に、景観映像は景観映像記憶部25に、それぞれ通過点毎に蓄積する。

#### 【0033】(5) 景観映像の表示

端末2は、センタ装置1から受信した景観映像をタッチパネル付表示部21のモニタ画面上に表示する。その際、経路記憶部24から読み出した目印ID117に対応する建物などをポインタ等で表示し、利用者が進むべき方向の発見を支援する。

【0034】さらに、端末2の制御部26は、設定時間毎にGPS信号による位置推定を行い、経路記憶部24に蓄積された通過点32に対して設定距離以下に近づいた時点で表示映像を切り替えたり、利用者が最適経路31から設定距離以上離れた時点で音声出力部27から警告音により知らせたりする等の処理を行う。

【0035】なお、前記実施形態例では位置推定にGPS信号を用いたが、地番表示の完備している市街地などでの利用を想定したGPS信号受信部を実装しない構成も可能である。

【0036】センタ装置と端末間の通信はPHSでモデム信号を用いる例を示したが、携帯電話で同様の構成をとることも可能である。また、PHSのデジタルデータ通信で実現することも可能である。

#### 【0037】

【発明の効果】以上説明したように、本発明によれば、

利用者は端末のモニタ画面上に表示される景観映像と実際の景観を見比べることにより容易に進むべき方向を見出すことができる。

【0038】また、センタ装置の景観映像は適宜更新可能であり、CD-ROMなどでは対応困難な最新情報/緊急情報の提供が可能となる。

【0039】また、景観映像を利用時間帯に分けて切り替えるようにした場合には、特に見通しの利かない夜間などでも容易に目的地に到着可能となる。

【0040】さらに、GPS等の位置検出手段を用いて現在地を特定するようにした場合には、特に、現在地が不明な場合にも道案内サービスが可能となる。

#### 【図面の簡単な説明】

【図1】本発明の一実施形態例を示すシステム構成図

【図2】上記実施形態例におけるシステムのセンタ装置のブロック構成図

【図3】上記実施形態例におけるシステムの端末のブロック構成図


【図4】上記センタ装置における位置データ/景観映像等管理部のフォーマットを示す図

【図5】上記実施形態例の動作説明図


#### 【符号の説明】

- 1…センタ装置
- 11…位置データ/景観映像等管理部
- 111…位置ID
- 112…方向ID
- 113…隣接位置ID
- 114…距離
- 115…目標ID
- 116…景観映像ID
- 117…目印ID
- 12…景観映像蓄積部
- 13…GPS信号受信部
- 14…回線制御部
- 15…最適経路選択部
- 16…制御部
- 2…端末
- 21…タッチパネル付表示部
- 22…GPS信号受信部
- 23…送受信部
- 24…経路記憶部
- 25…景観映像記憶部
- 26…制御部
- 27…音声出力部
- 31…最適経路
- 32…通過点
- 3…ISDN網
- 4…PHS公衆CS
- 5…端末

【図1】




【図2】






【図3】



【図5】



【図4】

111. 位置 ID	位置等管理データ				景観映像管理データ		
	112. 方向 ID	113. 隣接位置 ID	114. 距離	115. 目標 ID	時間帯	116. 景観映像 ID	117. 目印 ID
...	...	...	...	...		...	...
地名/地番	方向 ID1	地名/地番 p	距離 p	目標 i-1-1, i-1-2	日中	映像 i-1-1	115. に同じ
					夕暮れ	映像 i-1-2	目印 i-1-2
					夜間	映像 i-1-3	目印 i-1-2
	方向 ID2	地名/地番 q	距離 q	目標 i-2-1, i-2-2, i-2-3	日中	映像 i-2-1	115. に同じ
					夕暮れ	映像 i-2-2	目印 i-2-2, i-2-3
					夜間	映像 i-2-3	目印 i-2-2
	...	...	...	...		...	...
...	...	...	...	...		...	...
地名/地番 j	方向 ID1	地名/地番 x	距離 x	目標 j-1-1	日中	映像 j-1-1	115. に同じ
					夕暮れ	映像 j-1-2	115. に同じ
					夜間	映像 j-1-3	無し
	方向 ID2	地名/地番 y	距離 y	目標 j-2-1, j-2-2	日中	映像 j-2-1	目印 j-2-1
					夕暮れ	映像 j-2-2	目印 j-2-2
					夜間	映像 j-2-3	目印 j-2-2
	...	...	...	...		...	...
...	...	...	...	...		...	...